



## ES2000

*Flame-retardant, high-shrink-ratio, adhesive-lined semirigid polyolefin tubing*



### Applications

Specially designed for environmental sealing and electrical insulation of wire splices, terminations, and components.

### Operating temperature range

-40°C to 130°C

### Features and benefits

- 4:1 shrink ratio allows a few sizes to cover a wide range of splice and component diameters.
- Flame-retardant and mechanically tough, the tubing provides strain relief and abrasion protection of wire splices, terminals, and other components.
- Thick adhesive liner forms an effective barrier against fluids and moisture and performs well at an extended temperature range.
- UL recognized.

### Installation

Minimum shrink temperature: 110°C

Minimum full recovery temperature: 135°C

#### Available in:


Americas

Europe

Asia Pacific



#### Specifications/approvals

Series		Raychem
ES2000	E85381 600 V, 125°C	RT-1112

**Fax-on-demand**

US only (800) 260-9099  
 Outside US (650) 257-2301

**Fax ID**

2560  
 2561

**Description**

Data sheet  
 RT-1 1 1 2

Visit our website at [www.tycoelectronics.com](http://www.tycoelectronics.com)

**Product dimensions (mm/in)**

Part Number	Inside diameter (including core)		Recovered wall thickness*		
	Minimum expanded as supplied	Maximum recovered after heating	Minimum total wall after heating	Minimum jacket wall after heating	Minimum adhesive wall after heating
ES2000-No.1	5.72 (0.225)	1.27 (0.050)	1.20 (0.047)	0.64 (0.025)	0.56 (0.022)
ES2000-No.2	7.44 (0.293)	1.65 (0.065)	1.52 (0.060)	0.76 (0.030)	0.76 (0.030)
ES2000-No.3	10.85 (0.427)	2.41 (0.095)	1.91 (0.075)	0.89 (0.035)	1.02 (0.040)
ES2000-No.4	17.78 (0.700)	4.45 (0.175)	2.41 (0.095)	1.04 (0.041)	1.37 (0.054)

\*Wall thickness will be less if tubing recovery is restricted during shrinkage.

**Ordering information**

Color	Standard	Black (-0)
Size selection	Always order the largest size that will shrink snugly over the component to be covered.	
Standard packaging	Cut pieces.	
Marking	Tubing will be printed with its numbered size (such as ES-1, ES-2, ES-3, or ES-4).	
Ordering description	Specify product name, numbered size, color, and cut length (for example, ES2000-No. 2-0-50mm).	