



File E186611

Vol. 1

Issued: 8-26-97

Revised: 8-6-98

2600 N.W. Lake Road
Camas, WA 98607-8542
United States Country Code (1)
(360) 817-5500
FAX No. (360) 817-6000
<http://www.ul.com>

FOLLOW - UP SERVICE PROCEDURE
(TYPE R)



COMPONENT - TUBING - FLAME RETARDANT
(YDQS2)

* Manufacturer: SEE ADDENDUM FOR MANUFACTURING LOCATIONS

Applicant:
(333123-001)

Recognized
Company:
(333123-001)

This Procedure authorizes the above Manufacturer to use the marking specified by Underwriters Laboratories Inc. only on products covered by this Procedure, in accordance with the applicable Follow-Up Service Agreement.

The Prescribed Mark or Marking shall be used only at the above manufacturing location on such products which comply with this Procedure and any other applicable requirements.

The Procedure contains information for the use of the above named Manufacturer and the representatives of Underwriters Laboratories Inc. and is not to be used for any other purpose. It is lent to the Manufacturer with the understanding that it is not to be copied, either wholly or in part, and that it will be returned to Underwriters Laboratories Inc. upon request.

This PROCEDURE, and any subsequent revision, is the property of UNDERWRITERS LABORATORIES INC. and is not transferable.

UNDERWRITERS LABORATORIES INC.

S. Joe Bhatia
Vice President, Follow-Up Services

規格	折徑標準值	厚度標準值 x 0.01mm	橫向收縮%	縱向收縮%	高溫收縮(%)烤箱 180°C 15分鐘
3	5.5 $\begin{smallmatrix} + 0.1 \\ - 0.2 \end{smallmatrix}$	8.5 ± 1.0	49 ± 4	5~9	17 ± 3
4	7.2 ± 0.2	7.0 ± 1.0	49 ± 4	5~9	17 ± 3
4.9	9.0 $\begin{smallmatrix} + 0 \\ - 0.2 \end{smallmatrix}$	8.0 ± 1.0	49 ± 4	5~9	17 ± 3
5	9.1 ± 0.2	8.0 ± 1.0	49 ± 4	5~9	17 ± 3
6	10.5 ± 0.2	9.0 ± 1.0	49 ± 4	5~9	17 ± 3
6.2	10.8 $\begin{smallmatrix} + 0.1 \\ - 0.2 \end{smallmatrix}$	9.0 ± 1.0	49 ± 4	5~9	17 ± 3
6.3	11.0 ± 0.2	9.0 ± 1.0	49 ± 4	5~9	17 ± 3
7.9	13.7 $\begin{smallmatrix} + 0.3 \\ - 0 \end{smallmatrix}$	9.0 ± 1.0	49 ± 4	5~9	17 ± 3
8	14.0 ± 0.2	10 ± 1.0	49 ± 4	5~9	17 ± 3
10	17.0 ± 0.2	10 ± 1.0	46 ± 4	5~9	22 ± 3
12	20.7 ± 0.2	10 ± 1.5	46 ± 4	5~9	22 ± 3
12.5	21.6 ± 0.2	10 ± 1.5	46 ± 4	5~9	22 ± 3
13	22.1 ± 0.2	10 ± 1.5	46 ± 4	5~9	22 ± 3
16	27.2 ± 0.2	11 ± 1.5	46 ± 4	5~9	22 ± 3
18	30.1 ± 0.3	11 ± 1.5	46 ± 4	5~9	22 ± 3
20	33.2 ± 0.3	12 ± 1.5	46 ± 4	5~9	22 ± 3
22	36.3 ± 0.3	12 ± 1.5	46 ± 4	5~9	22 ± 3
25	41.4 ± 0.4	14 ± 2.0	46 ± 4	7.5~11.5	22 ± 3
30	49.5 ± 0.6	14 ± 2.0	46 ± 4	7.5~11.5	22 ± 3
35	57.4 ± 0.7	14 ± 2.0	46 ± 4	7.5~11.5	22 ± 3